



#### NOTES:

- \* Zinc alloy die cast housing and cylinder,chrome plated.
- \* Radial cylinder with 7 pin tumblers.
- \* Steel made tubular keys,nickel plated.
- \* Silver plated contacts and terminals.
- \* 2 Positions(off-on) 4 Terminals.(2NO. 2NC)
- \* All keyed alike or each 50 pcs in one combination.
- \* 10000 combinations available.
- \* Met with RoHS.

Recommended hole size

DATE	04.25.13	SCALE	2:1	UNIT	mm	WT. :	g	REV.:	A		DESCRIPTION	SWITCH LOCK
TOLERANCES		APPROVED BY		CHECKED BY		DRAWN BY					PART NO.	S206A-1
> 0.1	± 0.1										MATERIAL	.
> 0.2	± 0.2										NOTE	
> 0.3	± 0.3											
> 0.5	± 0.5											
> 1.0	± 1.0											
> 1.5	± 1.5											
> 2.0	± 2.0											
> 3.0	± 3.0											
> 4.0	± 4.0											
> 5.0	± 5.0											
> 6.0	± 6.0											
> 7.0	± 7.0											
> 8.0	± 8.0											
> 9.0	± 9.0											
> 10.0	± 10.0											

JICTEN